

PROFF OFFICE LACQUER



www.proffwoodcare.com

AREAS OF APPLICATION:

Proff-Office Lacquer floor varnish is water-based, almost odourless and exceptionally durable. Pro-Office Lacquer is based on a special polyurethane Hybrid binding agent with “self-crossing” properties which creates an incredibly durable and hard surface. The varnish can advantageously be used on stairs, kitchens, offices and corridors etc. It has a good chemical resistance, water resistance and good adhesion, even on floors which have been treated previously.

APPLICATION OF MATERIAL:

Proff-Office Lacquer floor varnish is used for indoor varnishing of untreated and previously treated wood such as parquet floors, panels, doors, stairs, natural cork, etc.

Remove dirt, grease, wax and soap. Then sand the wood with fine sandpaper (120 grit) until the wood has a matt surface. Remove the dust with a vacuum cleaner, the wood must then be washed with 3 deciliter 32% acetic acid in 10 liters of water to remove any wax residue – untreated or newly sanded floors must also be vacuumed thoroughly before varnishing. The wood has to dry before further treatment.

Apply the varnish undiluted with a roller or brush. After the varnish is dry, approximately 90 minutes, the wood can be sanded before the next 1-2 coats.

- A. It is important that both the wood and the varnish has the same temperature of a minimum 15° C, (20° C is best)
- B. As well as good ventilation to facilitate drying.
- C. Do not replace furniture or similar objects on the floor for at least 24 hours after the last coat.
- D. Rugs can be replaced on the new varnished floor after approximately eight days.
- E. Always remember to carry out tests to check that the wood and varnish are compatible.



PROFF WOODCARE PROFF OFFICE LACQUER



www.proffwoodcare.com

CONSUMPTION

Approx. 8-10 m² per liter, depending on wood condition

GLOSS

Gloss: Approx. 40

DISPOSAL

Empty containers and product residue disposed of according to regional rules and regulations.

STORAGE

Keep in tightly closed original packaging. Do not expose to heat (e.g. sunlight). Store frost-free and out the reach of children.

NOTE!

Please always make a test coat on the surface for controlling the compatability

